



Parallel Plate Line



*vertical
polarisation*



*horizontal
polarisation*

This parallel plate line is specially designed for the immunity test on small and medium-sized devices. It can also be used for specific tests according to the MIL-Standards. The main advantage of this line is that the equipment under test can easily be successively tested in both polarisations without being dismantled. The line is electrically symmetrical and the impedance is adapted through transformers on both sides. The line is very easy to pivot and to move. The dielectric table can be removed. An included metallic plate can be placed on the table depending on the requirements of the different standards. The parallel plate line can also be used for immunity tests on automotive devices according to the European directive 2004/104/EC and on broadcast receivers and associated equipment according to EN 55020. A simpler version without rotation and frame is also available (PPL200-70-S).

SPECIFICATIONS

Type	PPL200	PPL200-70-S
Polarisation	hor. and vertical	only vertical
Frequency range (± 1 dB)	10 kHz to 30 MHz	10 kHz to 30 MHz
Field homogeneity (in 0.4 m^3)	± 0.4 dB	± 1 dB
Maximum input power	500 W continuous 1 kW (20 min.)	500 W continuous 1 kW (20 min.)
Maximum field	320 V/m (@ 500 W)	450 V/m (@ 500 W)
Line / wave impedance	200Ω / 377Ω	200Ω / 377Ω
Input impedance	50Ω	50Ω
VSWR	< 2.5	< 2.5
Distance between plates	106 cm	70 cm
Total dimensions (L x W x H)	358 x 105 x 153 cm	370 x 100 x 76 cm
Total weight	150 kg	80 kg

Other models are available on request.